



Model : GV

Network Cabinet GV Series



Model : GV

Feature: tempered glass front door, vented split rear door.

GV Cabinet Package Contents:

- Cabinet Frame 2pcs
- Top Cover 1pc
- Glass Front door 1pc
- Cage nuts&screws 1bag
- Castor 4pcs
- Side Panel 2pcs
- Bottom Panel 1pc
- Vented split rear door 1 pair
- leveling feet 4pcs
- Keys 1set

Specification

Model No.	Capacity	Dimensions	Assembled Packaging (CBM)	Unassembled Packaging (CBM)
GV18-6060	18U	600*600 mm	0.40	0.17
GV18-6080	18U	600*800 mm	0.53	0.20
GV18-60100	18U	600*1000 mm	0.65	0.23
GV22-6060	22U	600*600 mm	0.49	0.20
GV22-6080	22U	600*800 mm	0.63	0.25
GV22-60100	22U	600*1000 mm	0.78	0.30
GV27-6060	27U	600*600 mm	0.57	0.23
GV27-6080	27U	600*800 mm	0.75	0.29
GV27-60100	27U	600*1000 mm	0.93	0.34
GV32-6060	32U	600*600 mm	0.66	0.28
GV32-6080	32U	600*800 mm	0.87	0.33
GV32-60100	32U	600*1000 mm	1.10	0.38
GV37-6060	37U	600*600 mm	0.75	0.30
GV37-6080	37U	600*800 mm	0.99	0.35
GV37-60100	37U	600*1000 mm	1.23	0.42
GV42-6060	42U	600*600 mm	0.84	0.32
GV42-6080	42U	600*800 mm	1.10	0.38
GV42-60100	42U	600*1000 mm	1.37	0.46
GV42-8080	42U	800*800 mm	1.50	0.43
GV42-80100	42U	800*1000 mm	1.82	0.54
GV42-80120	42U	800*1200 mm	2.16	0.61

- Standard: Comply with ANSI/EIARS-310-D, DIN41491; PART1, IEC297-2, DIN41494; PART7, GB/T3047.2-92 standard. Compatible with metric ETSI and 19 inch international standard.
- Material: Zinc plated mounting profiles, SPCC Cold rolled steel.
- Material thickness: Mounting profile: 2.0mm, mounting rails: 1.5mm, others: 1.2mm.
- Loading Capacity: 800kg.
- Protection grade: IP20.
- Ventilation Rate of Cabinet doors: $\geq 75\%$.
- Surface Finish: Degreasing, Pickling, Phosphating, Powder coating.
- Color: RAL9004(Black), RAL7035(Grey white).



OEM service



Door frame with vented holes



19" horizontal PDU



Grounding mark



Pre-punched holes for cabling



Cooling fan unit (optional)